

NOVEMBER 1999

HYDRASTAT

TECHNICAL INFORMATION SHEET

Hydrastat is a low VOC, water borne anti static high sheen floor paint, formulated to meet the requirements of television studios, which is easily removed by washing with Hydrawash.

The coating can be applied by a lambs wool roller to a clean dust free floor and is air dried within an hour, (depending upon environmental conditions)

TECHNICAL DATA

| | |
|--------------------------------|--|
| Colour | White |
| Non Volatile Content. (solids) | 54 ± 1 % |
| P.V.C. | 20.0 % |
| Sg at 20 °C | 1.2 |
| Viscosity | Ready to use. |
| Theoretical coverage. (75µm) | 7 - 8 M ² / L |
| Gloss | High sheen / gloss finish. |
| Shelf life | 12 months at ambient temperature. |
| | DO NOT ALLOW TO FREEZE |
| Cleaning of equipment water | Clean all equipment thoroughly with warm immediately after use. |

All Colours and Gloss Levels available.

GENERAL NOTE: It is important that this product is thoroughly evaluated under production conditions before being commercially adopted. (Such an evaluation should incorporate a reference to ageing). The above recommendations are made in good faith for the guidance of users and are without liability. Any queries should be referred to our Technical Sales Department.

Spraylat International Limited, 1 Bardsley Road, Earlstrees Industrial Estate, Corby, Northants NN17 4AR
Tel: 01536 408409; Fax: 01536 400410