

May 2000

SPRAYLAT DECKSTRIP (SHIPS)

TECHNICAL DATA

DESCRIPTION

Spraylat Deckstrip is a unique water borne, skin tight, peelable coating system designed to protect ship or boat decks during construction against minor abrasion and staining. It is weather resistant for several months and will perform over most non-porous surfaces including GRP and profiled non-skid painted surfaces.

HEALTH & SAFETY

Spraylat Deckstrip is LOW HAZARD AND NON-FLAMMABLE IN BOTH ITS LIQUID AND DRY FILM FORM (see separate Health & Safety Data).

APPLICATION

The system comprises two separate products – SIL330 a peelable base coat and SIL340 a weather resistant top coat. (For internal use the base coat may be used on its own). In order for the system to perform satisfactorily and remove as designed. IT IS IMPORTANT TO ENSURE THE CORRECT DRY FILM THICKNESS.

- Application may be Lambswool Ships Roller or by spray (conventional air or airless spray equipment with 21 thou tip size).
- Mask areas against overspray and avoid spraying into small openings where the coating may become thin and subsequently difficult to remove.
- Achieve a defined edge at the end of the area to be coated.
- Do not apply during rain or frost.
- A MINIMUM of two coats of basecoat will be required allowing the first coat to dry before applying the second.

DRYING TIME

Will vary according to humidity and temperature. Do not attempt to traffic the Spraylat until it has fully dried. The evaporation of water will be speeded up by air movement and warmth.

MINIMUM DRY FILM THICKNESS/COVERAGE

SIL330 basecoat - 300 microns DFT = 1m²/Kg (2 x 300 microns wet)
SIL340 topcoat - 125 microns DFT= 3m²/Kg (350 microns wet)

REMOVAL

Strip away by hand. Any difficult areas may be pressure washed away.

LONGEVITY

The coating will remain peelable for many months. In areas of heavy traffic it may be necessary to protect with matting. If the coating becomes torn lift the flap and reseal by brushing the underside with SIL330.

STORAGE

The shelf life of the liquid is 12 months. Store at temperatures between 5°C and 25°C. **DO NOT ALLOW TO FREEZE.**

COLOUR

SIL330: Light Grey. SIL340-1: Dark Grey.

CLEAN DOWN

Wash equipment immediately after use with clean water.

GENERAL NOTE: It is important that this product is thoroughly evaluated under production conditions before being commercially adopted (Such an evaluation should incorporate a reference to ageing). The above recommendations are made in good faith for the guidance of users and are without liability. Any queries should be referred to our Technical Sales Department.